



RS-16 & RS-16DC

Rotary Sanders

- Available in standard or dust control models
- Powerful 1.5 hp motor provides smooth operation and aggressive sanding
- Innovative "wiper" style switch keeps the motor contacts clean
- Smooth and rugged steel planetary gear systems
- Chrome plated steel housing, motor cover, and handle tube provide maximum durability
- Grey non-marking wheels and power cord protect the floor
- Grip face pad driver supplied with the machine

Because Pride Still Matters.

A Nilfisk-Advance Brand

Clarke[®]
American Sanders



SPECIFICATIONS	RS-16	RS-16DC
Part Number	07161A	07162A
Pad Diameter	16 in	
Pad Speed	175 RPM	
Voltage	120 V / 60 Hz	
Horsepower	1.5 hp (1.1 kW)	
Motor	Dual capacitor induction	
Gear Box	Triple planetary	
Power Cord	50 ft, 14-3 non-marking grey	
Frame	Die cast aluminum alloy	
Wheels	5 in (12.7 cm) non-marking grey	
Dust Skirt	NA	Reinforced nylon, quick removal
Dust Hose	NA	1.5 in (36 mm)
Weight	91 lb (41.3 kg)	95 lb (43 kg)
Warranty	5 Years	

Specifications are subject to change without notice.



The simple modular switch design allows fast and easy repairs to minimize maintenance.



Powerful 1.5 hp motor has dual capacitors to maximize startup and run torque.



The wide stance of the transport wheels promote maximum stability when rolling over thresholds.



The **PDC Essential** package features the RS-16DC Disc Sander and the CAV 12 Tank Vacuum along with the standard vacuum tool kit.

- PN 11160A



recyclable

14600 21st Avenue North • Plymouth, MN 55447-3408
Phone: 800.253.0367 • Fax: 800.825.2753

240 Superior Boulevard • Mississauga, Ontario, Canada L5T 2L2
Phone: 800.668.8400 • Fax: 800.263.5111

Clarke®
American Sanders